

# Distance-based Multimedia Indexing

Christian Beecks  
Data Management and Data  
Exploration Group  
RWTH Aachen University,  
Germany  
beecks@cs.rwth-  
aachen.de

Merih Seran Uysal  
Data Management and Data  
Exploration Group  
RWTH Aachen University,  
Germany  
uysal@cs.rwth-  
aachen.de

Thomas Seidl  
Database Systems Group  
Ludwig-Maximilians-  
Universität Munich,  
Germany  
seidl@dbs.ifi.lmu.de

## ABSTRACT

This tutorial aims at providing an overview of the state-of-the-art approaches to distance-based multimedia indexing. This tutorial presents the fundamentals of (i) object representation, (ii) distance-based similarity models, (iii) efficient query processing, and (iv) indexing. It is intended for a broad target audience starting from beginners to experts in the domain of distance-based similarity search in multimedia databases and adjacent research fields which utilize distance-based approaches.

## 1. INTRODUCTION

Concomitant with the explosive growth of the digital universe [11], an immensely increasing amount of multimedia data is generated, processed, and finally stored in very large multimedia databases. The rapid expansion of the internet and the extensive spread of mobile devices allow users to generate and share multimedia data everywhere and at any time. As a result, multimedia databases tend to grow continuously without any restriction and are thus no longer manually manageable by humans. Automatic approaches that allow for effective and efficient information access to massive multimedia databases become immensely important.

*Multimedia retrieval approaches* are one class of information access approaches that allow to manage and access multimedia databases with respect to the users' information needs. These approaches deal with the representation, storage, organization of, and access to information items [2]. In fact, they can be thought of approaches allowing users to *search*, *browse*, *explore*, and *analyze* multimedia databases by means of similarity relations among multimedia objects.

One promising and widespread approach to define similarity between multimedia objects consists in automatically extracting inherent properties of multimedia objects and comparing them with each other. For this purpose, the content-based properties of multimedia objects are modeled by feature representations which are comparable by means of *distance-based similarity measures*. This class of similarity

measures follows a rigorous mathematical interpretation [19] and allows domain experts and database experts to address the issues of effectiveness and efficiency simultaneously and independently. In fact, it has become mandatory for current distance-based similarity measures to be indexable in order to facilitate large-scale applicability.

## 2. TUTORIAL OUTLINE

In this tutorial, we aim at providing an overview of the state-of-the-art approaches to distance-based multimedia indexing. We intend to cover a broad target audience starting from beginners to experts in the domain of distance-based similarity search in multimedia databases and adjacent research fields which utilize distance-based approaches. No prerequisite knowledge is needed.

### 2.1 Object Representation

In the first part of this tutorial, we will outline different approaches to object representations in order to answer the question of how to model multimedia data objects in a generic way. We will focus on a unified object representation model including fixed-binning feature histograms and adaptive-binning feature signatures [3]. In addition to these object representations, we will present the idea of probabilistic feature signatures [4, 5] and show how to approximate object representations by means of gradient-based signatures [7].

### 2.2 Distance-based Similarity Models

In the second part of this tutorial, we will provide an overview of state-of-the-art distance-based similarity measures for feature histograms and feature signatures in order to complete our understanding of a similarity model. Among the multitude of distance-based similarity measures applicable to feature signatures, we will present and discuss the Earth Mover's Distance [15], the Signature Quadratic Form Distance [8], and the Signature Matching Distance [6].

### 2.3 Efficient Query Processing

The third part of this tutorial is devoted to techniques and algorithms for efficient query processing. After introducing distance-based similarity queries, we show how to process such queries efficiently by means of multi-step filter-and-refinement algorithms including multi-step range query algorithms [10] and optimal multi-step  $k$ -NN query algorithms [18]. To this end, we elucidate the idea of lower bound approximations and present state-of-the-art lower bound approximations [1, 20, 21] for the Earth Mover's Distance.

## 2.4 Indexing

The last part of this tutorial finally covers indexing approaches for distance-based similarity models where we will give an insight into the fundamentals of spatial access methods [16, 22], metric access methods [9, 14, 17, 23], and ptolemaic access methods [12, 13].

## 3. FURTHER INFORMATION

Further information regarding this tutorial can be found at <http://dme.rwth-aachen.de/en/DBMI>.

## 4. ACKNOWLEDGMENTS

This work is funded by DFG grant SE 1039/7-1. It is partly based on the work of Beecks [3].

## 5. REFERENCES

- [1] I. Assent, A. Wenning, and T. Seidl. Approximation techniques for indexing the earth mover's distance in multimedia databases. In *ICDE*, pages 11:1–12, 2006.
- [2] R. Baeza-Yates and B. Ribeiro-Neto. *Modern Information Retrieval*. Addison Wesley Professional, 2011.
- [3] C. Beecks. *Distance-based similarity models for content-based multimedia retrieval*. PhD thesis, RWTH Aachen University, 2013.
- [4] C. Beecks, A. M. Ivanescu, S. Kirchhoff, and T. Seidl. Modeling image similarity by gaussian mixture models and the signature quadratic form distance. In *ICCV*, pages 1754–1761, 2011.
- [5] C. Beecks, A. M. Ivanescu, S. Kirchhoff, and T. Seidl. Modeling multimedia contents through probabilistic feature signatures. In *ACM Multimedia*, pages 1433–1436, 2011.
- [6] C. Beecks, S. Kirchhoff, and T. Seidl. Signature matching distance for content-based image retrieval. In *ICMR*, pages 41–48, 2013.
- [7] C. Beecks, M. S. Uysal, J. Hermanns, and T. Seidl. Gradient-based signatures for efficient similarity search in large-scale multimedia databases. In *CIKM*, pages 1241–1250, 2015.
- [8] C. Beecks, M. S. Uysal, and T. Seidl. Signature quadratic form distance. In *CIVR*, pages 438–445, 2010.
- [9] E. Chávez, G. Navarro, R. A. Baeza-Yates, and J. L. Marroquín. Searching in metric spaces. *ACM Computing Surveys*, 33(3):273–321, 2001.
- [10] C. Faloutsos, M. Ranganathan, and Y. Manolopoulos. Fast subsequence matching in time-series databases. In *SIGMOD*, pages 419–429, 1994.
- [11] J. F. Gantz, C. Chute, A. Manfrediz, S. Minton, D. Reinsel, W. Schlichting, and A. Toncheva. The diverse and exploding digital universe. *IDC White Paper*, 2, 2008.
- [12] M. L. Hetland. Ptolemaic indexing. *JoCG*, 6(1):165–184, 2015.
- [13] M. L. Hetland, T. Skopal, J. Lokoč, and C. Beecks. Ptolemaic access methods: Challenging the reign of the metric space model. *Information Systems*, 38(7):989 – 1006, 2013.
- [14] G. R. Hjaltason and H. Samet. Index-driven similarity search in metric spaces. *ACM Transactions on Database Systems*, 28(4):517–580, 2003.
- [15] Y. Rubner, C. Tomasi, and L. J. Guibas. The earth mover's distance as a metric for image retrieval. *IJCV*, 40(2):99–121, 2000.
- [16] H. Samet. *The design and analysis of spatial data structures*. Addison-Wesley Reading, MA, 1990.
- [17] H. Samet. *Foundations of multidimensional and metric data structures*. Morgan Kaufmann, 2006.
- [18] T. Seidl and H.-P. Kriegel. Optimal multi-step k-nearest neighbor search. In *SIGMOD*, pages 154–165, 1998.
- [19] R. N. Shepard. Stimulus and response generalization: A stochastic model relating generalization to distance in psychological space. *Psychometrika*, 22:325–345, 1957.
- [20] M. S. Uysal, C. Beecks, D. Sabinasz, J. Schmücking, and T. Seidl. Efficient query processing using the earth mover's distance in video databases. In *EDBT*, 2016.
- [21] M. S. Uysal, C. Beecks, J. Schmücking, and T. Seidl. Efficient filter approximation using the earth mover's distance in very large multimedia databases with feature signatures. In *CIKM*, pages 979–988, 2014.
- [22] P. van Oosterom. Spatial access methods. *Geographical information systems*, 1:385–400, 1999.
- [23] P. Zezula, G. Amato, V. Dohnal, and M. Batko. *Similarity Search - The Metric Space Approach*. Advances in Database Systems. Kluwer, 2006.